

Version 2.0	Revision Date: 06/08/2018	SDS Number: 000000605360
SECTION 1. IDENTIFICATI	ION	
Product name	<sup>:</sup> Sarnacol <sup>®</sup> -2170 F	२
Manufacturer or supp	plier's details	
Company name	: 601, avenue Delma Canada Pointe-Claire, QC Sika Canada Inc. www.sika.ca	
Telephone	: (514) 697-2610 / 1	(800) 933-7452
Telefax	: (514) 694-2792	
Health and Safety Servermetry e-mail address	vices's : ehs@ca.sika.com	
Emergency telephone	: CANUTEC (collect	t) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use

For further information, refer to product data sheet.

### **SECTION 2. HAZARDS IDENTIFICATION**

GHS Classification Flammable liquids	:	Category 2
Skin irritation	:	Category 2
Eye irritation	:	Category 2A
Carcinogenicity (Inhalation)	:	Category 2
Reproductive toxicity	:	Category 2
Effects on or via lactation		
Specific target organ system- ic toxicity - single exposure	:	Category 3 (Central nervous system)
Specific target organ system- ic toxicity - repeated expo- sure (Inhalation)	:	Category 2

### **GHS** label elements



rsion )	Revision Date: 06/08/2018	SDS Number: 00000605360		
Hazard pictograms				
Signal Word	: Danger	•		
Hazard Statements	<ul> <li>Hazard Statements</li> <li>H225 Highly flammable liquid and vapor. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer if inhaled. H361 Suspected of damaging fertility or the unborn ch H362 May cause harm to breast-fed children. H373 May cause damage to organs through prolonger peated exposure if inhaled.</li> </ul>			
Precautionary Statements	<ul> <li>P201 Obtain special</li> <li>P202 Do not handle</li> <li>and understood.</li> <li>P210 Keep away fro</li> <li>and other ignition so</li> <li>P233 Keep containe</li> <li>P240 Ground and bo</li> <li>P241 Use explosion</li> <li>ment.</li> <li>P242 Use non-spark</li> <li>P243 Take action to</li> <li>P260 Do not breather</li> <li>P263 Avoid contact</li> <li>P264 Wash skin tho</li> <li>P270 Do not eat, dri</li> <li>P271 Use only outdot</li> <li>P280 Wear protective</li> <li>face protection.</li> <li><b>Response:</b></li> <li>P303 + P361 + P352</li> <li>all contaminated clost</li> <li>P304 + P340 + P312</li> <li>and keep comfortable</li> <li>CENTER/doctor if yot</li> <li>P305 + P351 + P338</li> <li>for several minutes.</li> <li>to do. Continue rinsi</li> <li>P308 + P313 IF explatention.</li> <li>P337 + P313 If skin</li> <li>tion.</li> <li>P362 + P364 Take or</li> <li>reuse.</li> </ul>	r tightly closed. ond container and receiving equipment. proof electrical/ ventilating/ lighting/ equip ing tools. prevent static discharges. e dust/ fume/ gas/ mist/ vapors/ spray. during pregnancy and while nursing. roughly after handling. hk or smoke when using this product. pors or in a well-ventilated area. e gloves/ protective clothing/ eye protection B IF ON SKIN (or hair): Take off immediate hing. Rinse skin with water. 2 IF INHALED: Remove person to fresh ai e for breathing. Call a POISON pu feel unwell. 3 IF IN EYES: Rinse cautiously with water Remove contact lenses, if present and ea		



Version 2.0	Revision Date: 06/08/2018	SDS Number: 000000605360
	tightly closed. P403 + P235 Store in P405 Store locked up <b>Disposal:</b>	a well-ventilated place. Keep container a well-ventilated place. Keep cool.
Warning	some of the chemical kidney and nervous s	ted repeated and prolonged exposure to s in this product with permanent brain,liver, ystem damage. Intentional misuse by de- and inhalation of vapors may be harmful
Other hazards None known.		

#### Supplemental information

If product is in liquid or paste form, physical or health hazards listed related to dust are not considered significant. However, product may contain substances that could be potential hazards if caused to become airborne due to grinding, sanding or other abrasive processes.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
butanone	78-93-3	>= 30 - < 60
Toluene	108-88-3	>= 15 - < 40
xylene	1330-20-7	>= 2 - < 5
ethylbenzene	100-41-4	>= 1 - < 2
alkanes, C14-17, chloro	85535-85-9	>= 0 - < 1

### SECTION 4. FIRST AID MEASURES

General advice	<ul> <li>Move out of dangerous area.</li> <li>Consult a physician.</li> <li>Show this material safety data sheet to the doctor in atternative ance.</li> </ul>	∍nd-
If inhaled	: Move to fresh air. Consult a physician after significant exposure.	
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.	
In case of eye contact	<ul> <li>Immediately flush eye(s) with plenty of water.</li> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> </ul>	



Version 2.0	Revision Date: 06/08/2018	SDS Number: 000000605360
If swallowed	Do not induce vomiting v Do not give milk or alcoh	and drink afterwards plenty of water. without medical advice. holic beverages. nouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	d Respiratory disorder Excessive lachrymation Erythema Dermatitis Loss of balance Vertigo See Section 11 for more and symptoms. Causes skin irritation. Causes serious eye irrita May cause drowsiness of Suspected of causing ca Suspected of damaging May cause harm to brea	or dizziness. Incer if inhaled. fertility or the unborn child.
Notes to physician	: Treat symptomatically.	

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	cohol-resistant foam rbon dioxide (CO2) / chemical	
Unsuitable extinguishing media	ater jh volume water jet	
Specific hazards during fire fighting	not use a solid water stream	as it may scatter and spread
Further information	e water spray to cool unopene llect contaminated fire extinguist not be discharged into drai e residues and contaminated disposed of in accordance wi	uishing water separately. This ns. fire extinguishing water must
Special protective equipment for fire-fighters	the event of fire, wear self-cor	ntained breathing apparatus.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : Use personal protective equipment.



Version 2.0	Revision Date: 06/08/2018	SDS Number: 000000605360
tive equipment and emer- gency procedures	Deny access to unpro	tected persons. umulating to form explosive concentra-
Environmental precautions	If the product contamine respective authorities.	nates rivers and lakes or drains inform
Methods and materials for containment and cleaning	up sorbent material, (e.g.	then collect with non-combustible ab- sand, earth, diatomaceous earth, ver- container for disposal according to local (see section 13).

### SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take pre- cautionary measures against electrostatic discharges.
Advice on safe handling	<ul> <li>Do not breathe vapors or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Follow standard hygiene measures when handling chemical products.</li> </ul>
Conditions for safe storage	<ul> <li>Store in original container.</li> <li>Store in cool place.</li> <li>Keep in a well-ventilated place.</li> <li>Containers which are opened must be carefully resealed and kept upright to prevent leakage.</li> <li>Observe label precautions.</li> <li>Store in accordance with local regulations.</li> </ul>

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
butanone	78-93-3	TWA	200 ppm	CA AB OEL



SDS Number:

# Sarnacol®-2170 R

Version 2.0

Sion	06/08/2018		0000006053	
			590 mg/m3	
		STEL	300 ppm 885 mg/m3	CA AB OEL
		TWA	50 ppm	CA BC OEL
		STEL	100 ppm	CA BC OEL
		TWAEV	50 ppm 150 mg/m3	CA QC OEL
		STEV	100 ppm 300 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
Toluene	108-88-3	TWA	50 ppm 188 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 188 mg/m3	CA QC OEL
		TWA	20 ppm	ACGIH
xylene	1330-20-7	TWA	100 ppm 434 mg/m3	CA AB OEL
		STEL	150 ppm 651 mg/m3	CA AB OEL
		TWAEV	100 ppm 434 mg/m3	CA QC OEL
		STEV	150 ppm 651 mg/m3	CA QC OEL
		TWA	100 ppm	CA BC OEL
		STEL	150 ppm	CA BC OEL
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
ethylbenzene	100-41-4	TWA	100 ppm 434 mg/m3	CA AB OEL
		STEL	125 ppm 543 mg/m3	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	100 ppm 434 mg/m3	CA QC OEL
		STEV	125 ppm 543 mg/m3	CA QC OEL
		TWA	20 ppm	ACGIH
		STEL	125 ppm	ACGIH

Revision Date:

### **Biological occupational exposure limits**

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra- tion	Basis
butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to	0.02 mg/l	ACGIH



SDS Number:

00000605360

# Sarnacol®-2170 R

Version 2.0 Revision Date: 06/08/2018

	00/00/201	•			0000000	
				last shift of work- week		BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
xylene	1330-20-7	Methylhip- puric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g cre- atinine	ACGIH BEI
butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work- week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
xylene	1330-20-7	Methylhip- puric acids	Urine	End of shift (As soon as possible after	1.5 g/g cre- atinine	ACGIH BEI



sion	Revision 06/08/201		SDS Number: 000000605360			
				exposure ceases)		
ethylbenzene	100-41-4	Sum of mandelic acid and phenyl gly- oxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGII BEI
Engineering measures : Use of adequate worker exposure to product generates cess enclosures, ing controls to kee ed or statutory lime. The engineering of dust concentration.		to airborne c s dust, fume local exhaus ep worker ex nits. controls also	contaminant s, gas, vapo st ventilation (posure bel need to ke	ts. If the use c or or mist, use or or other eng ow any recom ep gas, vapor	of this pro- ineer- imend-	
Personal protective equ	ipment					
Respiratory protection	res	e a properly fit pirator comply ssment indicate	ring with an a	approved st		
	imu (ga dlir	e filter class fo um expected c is/vapor/aerosi ng the product. ntained breathi	ontaminant o ol/particulate If this conce	concentrations) that may	on <sup>,</sup> arise when h exceeded, sel	an-
Hand protection						
Remarks	apı che	emical-resistar proved standar emical product sary.	rd should be	worn at all	times when h	andling
Eye protection		fety eyewear c used when a r				
Skin and body protection	trat	oose body pro tion and amou c work-place.				
Hygiene measures	Wa the Re hav Re bel	bid contact with ash hands befor product. move respirato ve been cleare move contamin fore entering e ash thoroughly	ore breaks ar ory and skin/ d from the a nated clothin ating areas.	nd immedia eye protect rea. Ig and prote	tely after hand	vapors



Version	Revision Date:	SDS Number:
2.0	06/08/2018	00000605360

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	amber
Odor	:	characteristic
Odor Threshold	:	No data available
рН	:	Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	111 °C (232 °F)
Flash point	:	ca5 °C (23 °F) Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit	:	7 %(V)
Lower explosion limit	:	1 %(V)
Vapor pressure	:	88.9924 hpa (66.750 mmHg)
Relative vapor density	:	No data available
Density	:	ca. 0.888 g/cm3 (23 °C (73 °F) ())
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. > 20.5 mm2/s (40 °C)
Explosive properties	:	No data available
Molecular weight	:	No data available



Version 2.0	Revision Date: 06/08/2018	SDS Number: 000000605360

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.				
Chemical stability	: The product is chemically stable.				
Possibility of hazardous reac- tions	: Stable under recommended storage conditions. Vapors may form explosive mixture with air.				
Conditions to avoid	: Heat, flames and sparks.				
Incompatible materials	: No data available				
No decomposition if stored and applied as directed.					

#### SECTION 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

Not classified based on available information.

Pr	od	uc	t:
_			

Acute oral toxicity	Acute toxicity estin Method: Calculation	mate: > 5,000 mg/kg on method
Acute inhalation toxicity	Acute toxicity estin Exposure time: 4 Test atmosphere: Method: Calculation	h vapor
Acute dermal toxicity	Acute toxicity estin Method: Calculation	mate: > 5,000 mg/kg on method
Ingredients:		
<b>butanone:</b> Acute oral toxicity	LD50 Oral (Rat): 3	3 300 ma/ka
-		
Acute inhalation toxicity	LC50 (Rat): 36 mg Exposure time: 4 Test atmosphere:	ĥ
Acute dermal toxicity	LD50 Dermal (Ra	bbit): > 5,000 mg/kg
xylene:		
Acute oral toxicity	LD50 Oral (Rat): 3	3,523 mg/kg
Acute dermal toxicity	LD50 Dermal (Ra	bbit): 1,700 mg/kg
ethylbenzene:		
Acute oral toxicity	LD50 Oral (Rat): 3	3,500 mg/kg
Acute dermal toxicity	LD50 Dermal (Ra	bbit): 5,510 mg/kg



/ersion 2.0	Revision Date: 06/08/2018	SDS Number: 000000605360
Skin corrosion/irri Causes skin irritatio		
Serious eye dama Causes serious eye		
	<b>n sensitization</b> Not classified based on available info zation: Not classified based on availal	
Germ cell mutage Not classified base	<b>nicity</b> d on available information.	
Carcinogenicity		
	ng cancer if inhaled. Group 2B: Possibly carci	inogenic to humans
	ethylbenzene	100-41-4
NTP	Not applicable	
Reproductive toxi	city	
	iging fertility or the unborn child. breast-fed children.	
STOT-single expo	sure	
May cause drowsin	ess or dizziness.	
STOT-repeated ex	posure	
May cause damage	e to organs through prolonged or repe	eated exposure if inhaled.
Aspiration toxicity	/	
Not classified base	d on available information.	
ECTION 12. ECOLOG		
Ecotoxicity		
<u>Ingredients:</u> xylene:		
Toxicity to fish	: LC50 (Oncorhynchus Exposure time: 96 h	mykiss (rainbow trout)): 3.3 mg/l
Persistence and d	egradability	

No data available

**Bioaccumulative potential** 

No data available

Mobility in soil

No data available

Other adverse effects

#### Product:



Version	Revision Date:	SDS Number:
2.0	06/08/2018	000000605360
Additional ecological infor- mation	: Do not empty into drains; dispose tainer in a safe way. Avoid dispersal of spilled materia soil, waterways, drains and sewe	l and runoff and contact with

### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	Disposal of this product, solutions and any by-produ at all times comply with the requirements of environ protection and waste disposal legislation and any re local authority requirements.	mental
Contaminated packaging	Empty containers should be taken to an approved w dling site for recycling or disposal.	aste han-

### SECTION 14. TRANSPORT INFORMATION

### **Domestic regulation**

<b>TDG (road/train)</b> UN number Proper shipping name	: UN 1133 : ADHESIVES
Class Packing group Labels	: 3 : II : 3
International Regulations	
IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passen- ger aircraft)	: UN 1133 : Adhesives : 3 : II : Flammable Liquids : 364 : 353
<b>IMDG-Code</b> UN number Proper shipping name	: UN 1133 : ADHESIVES
Class Packing group Labels EmS Code Marine pollutant	: 3 : II : 3 : F-E, S-D : no



Version	Revision Date:	SDS Number:
2.0	06/08/2018	00000605360

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### SECTION 15. REGULATORY INFORMATION

Canadian PBT Chemicals	<ul> <li>This product contains the following components on the DSL that are classified as Persistent, Bioaccumulative and/or Toxic (PBT) under CEPA: alkanes, C14-17, chloro</li> </ul>
Canadian lists	

No substances are subject to a Significant New Activity Notification.

### SECTION 16. OTHER INFORMATION

**Revision Date** 

: 06/08/2018

Prepared by : R & D of Sika Canada Inc.

Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

#### Full text of other abbreviations

ADR	Accord européen relatif au transport international des marchandises
	Dangereuses par Route
CAS	Chemical Abstracts Service
DNEL	Derived no-effect level
EC50	Half maximal effective concentration
GHS	Globally Harmonized System
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Code for Dangerous Goods
LD50	Median lethal dosis (the amount of a material, given all at once, which
	causes the death of 50% (one half) of a group of test animals)
LC50	Median lethal concentration (concentrations of the chemical in air that
	kills 50% of the test animals during the observation period)
MARPOL	International Convention for the Prevention of Pollution from Ships, 1973
	as modified by the Protocol of 1978



Version	Revision Date:	SDS Number:	
2.0	06/08/2018	000000605360	
OEL	Occupational Exposure Limit		
PBT	Persistent, bioaccumulative and toxic		
PNEC	Predicted no effect concentration		
REACH	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency		
SVHC	Substances of Very High Concern		
vPvB	Very persistent and very bioaccumulative		

CA / Z8